

APPLICATION



If contaminated, use a claybar to clean the paint and wheels. If paint correction is required do so before application.



Wash and completely dry surfaces to be coated.



Clean the paint using a 50% IPA (isopropyl alcohol) to water mix in a trigger sprayer. Mist the paint then wipe down with a microfiber towel.



Wipe on coating by hand using a sponge or coating block, panel by panel. After wiping on wait 30-90 seconds to flash (depending on temp) then buff off with a microfiber towel.



Wait 20 minutes before driving, and 4 hours before getting wet.

CRYSTAL^{SS}
CERAMIC NANO COATING

PRODUCT OVERVIEW



System X Crystal Ceramic Coating is a professional grade coating that lasts for up to 3 years – that offers superior System X Crystal semi-permanent ceramic coating, provides 2-3 years of gloss and protection.

Crystal inter-locks part of its molecular structure with the surface molecules of your paintwork so you get a coating that will not be washed off like a wax or sealant. Crystal has passed rigorous Boeing approval testing which ensures 100% safety for paint.

Utilizing our proprietary ceramic technology Crystal is high performer against friction, heat, and solvents.



TECHNICAL DATA

EFFECTIVENESS	3 years depending on environmental factors
PENCIL HARDNESS	9H
APPLICATION	By hand with sponge, coating block or cotton applicator
BOTTLE SIZE	65 mL, 275ml
SHELF TIME	1 years from shipment date when unopened and stored dry at 18°C (64°F) to 23°C (73°F)
APPEARANCE	Clear / High Gloss
FILM THICKNESS	0.15 - 0.2 mil
MANDREL BEND	(ASTM D522) 0% @ 180° rotation
CHEM. RESISTANCE	Very Good
TEMP. RESISTANCE	> 760°C (1400°F)
ADHESION CROSS-CUT TAPE	(ASTM D3359) 5b (0%, none)
COVERAGE	60 sqft / ounce (30 ml)
DRY TIME	20 minutes
CURE TIME	Initial cure in 4 hours, full cure in 3 days